TRACKER RX

TRACKER VERSION RX

Bollé Safety offers a simple and flexible system, based on a unique pricing. The RX range is composed of a wide range of frames that can be glazed with 3 types of prescription lenses (single vision, bifocal, progressive) and 3 different lens materials (polycarbonate, CR39 or toughened glass).







Ref. TRACKERRX + SOSTRACKER

52 g

SUPPLIED WITH

Hard case, microfibre cloth

FRAME

"Plastic" Polycarbonate LENS MATERIAL AVAILABLE

- Polycarbonate
- CR39



- **UPPER AND LOWER PROTECTION**
- **# INTERCHANGEABLE FOAM**
- **+** ADJUSTABLE STRAP



TRACKER RX

TRACKER VERSION RX

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
TRACKERRX	PC / Black	TRACKERRX	56/26	≅ EN166 FC€	117 mm

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power +4/-4.

Maximum cylinder compared with sphere: +/-3.

CORRECTED BASE:

Corrected base: 6

PACKAGING AND EAN13 CODE			
	TRACKERRX		
Per piece	3660740000042		

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

C€ European standard Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENS	CR39, Polycarbonate			
TYPES OF CORRECTIONS AVAILABLE	Single vision Bifocal Progressive			
FRAME	Polycarbonate / Black			
STRAP	Polyester			
FOAM	EVA			









21/07/2016

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

